

HMC9000-Li(24) Battery

Features:

- Up to 20% lower operating cost.
- Provides more charge cycles.
- Longer battery life.
- Full shift operation.
- Reinforced contact assembly to ensure uninterruptible scanning.
- Uses the highest quality graded and sorted battery cells.
- Stronger, high impact polymer case.
- Rigorous testing including altitude simulation, temperature, vibration, shock, drop, short circuit and overcharge.
- ETL Listed.

Cell Specifications

Chemistry: Industrial Lithium Ion

Voltage: 7.4 Volts
Capacity: 2400 mAh

Environmental Data

Charging Temp.: 0° - 50° C (32° F to 122° F)

Discharging Temp.: -20° - 60° C (-4° F to 140° F)

Storage Temp.: -20° - 50° C (-4° F to 122° F)

Battery Dimensions

Length:	74.6 mm
Width (top):	41.4 mm
Height:	24.2 mm
Weight:	122.0 g

Rechargeable battery for Symbol MC90XX Series devices.

Replaces OEM **21-65587-01** and **KT-21-61261-01** batteries.





Each battery is guaranteed to be free from defects in materials and workmanship and can maintain a minimum of 80% of its rated capacity for 12 months from date of shipment under normal use.

About Us

Global Technology Systems, Inc. ("GTS") is the trusted expert in mobile power technology. GTS designs and manufactures high-performance batteries, chargers, and power management technologies for essential mobile devices. Millions of public safety, government, military, and business professionals rely on GTS to power mission critical communications and mobile computing applications. Founded in 2000, GTS is headquartered in Framingham, Massachusetts.



For Pricing or Additional Information Contact: Global Technology Systems, Inc. 550 Cochituate Road Framingham, MA 01701