## **Charger Specifications:**

Input Voltage: 10V - 32V DC

Input Current: 1Amp Max

Output Voltage: 4.65V DC

Output Current: 1.5Amp Max

Operating Temp: 0°C - 40°C

(32°F - 104°F)

Storage Temp: -10°C - 50°C

(15°F - 125°F)

Charging Time: Determined by Device

#### **Dimensions:**

Length: 2 inches (51 mm)
Width: 3.1 inches (80 mm)
Height: 3.4 inches (87 mm)

**Excluding Power Cord** 

Power Cord Length: 2 feet Weight: 242 g

(Including Power Cord)

### Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 12 months from date of shipment under normal use.



### **Global Technology Systems**

# **HCH-CN50-DC**

DC Travel Charger for Intermec® CN50/CN51 Mobile Computer



#### Features:

- Light weight, versatile and portable design for in-vehicle use.
- Includes power supplies and cable.
- Compatible with RAM Mount.
- Cup has reinforced pins to avoid easy breakage.
- Connectors and cigarette lighter plug have been improved to industrial grade and reinforced from original design.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc. 550 Cochituate Road Framingham, MA 01701 US: 1.800.267.2711 ■ EU: 00800.5390.5390

www.GTSpower.com @GTSpower1

