

HCH-7033-CHG

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to 40°C
32°F to 104°F

Storage Range: -10°C to 50°C
-14°F to 122°F

Dimensions:

Length: 420 mm
Width: 160 mm
Height: 114 mm
Weight: 1150 g

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



Compatible Batteries

- HMC70-Li(22) GTS Battery
- HMC70-Li(36) GTS Battery
- HMC70-Li(48) GTS Battery

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

14.03.28

Maximize performance with GTS MC70/MC75 Cradle & Battery Charger

Made of highly rugged aerospace grade aluminum housing.

Includes power supplies and cable.

Dual-chemistry charger
Supports Li-Ion and Li-Polymer chemistries.



More efficiency in less space
Charges 50% more batteries in same space as OEM chargers.

Tri-color charging indications
A charging LED indicates charging status.



Hassle-free mounting
Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com @GTSpower1

